



5150-5350 MHz Collinear antennas A-8Y, A-11Y

107497, Moscow Chernicinsky pr-d 7/1
Tel.: (495) 775-43-19, 462-44-14
Tel./fax: 462-44-14
E-mail: radial@radial.ru
www.radial.ru



Electrical specifications

Model	A-8Y	A-11Y
Operating frequency band, MHz	5150-5350	5150-5350
Gain, dBi	8	11
VSWR, not more than	1.5	1.5
Polarization		vertical
Electrical downtilt	3°	7°
Max. power input, W	10	10
Sector in H-plane (-3 dB)	360°	360°
Sector in E-plane (-3 dB)	14°	7°
Impedance, Ohm	50	50

Mechanical specifications

Model	A-8Y	A-11Y
Dimensions (LxWxH), mm	35x35x370	35x35x810
Weight, kg	0.1	0.25
Rated wind velocity, m/s	50	50
Radiator	PCB	PCB
Radome	grey PVC	grey PVC
Mounting kit CPK-70		on a mast 35-70 mm or on wall
Connector		N-female

The vertical antennas A-8Y and A-11Y possess an increased gain (8 and 11 dBi), an ideally circular radiation pattern, small electrical tilt of the beam in a vertical plane. Their construction is formed by an antenna array with consequent feeding of the elements on the printed circuit board, implemented on the SHF material, which is characterized by a small value of the dielectric losses. The printed circuit boards are also plated by an SHF-lacquer, and the radome is encapsulated.

