




**140-154, 148-163, 158-174 MHz
Isolators "extreme"
IF-1(2)VL-50(125)X/2, IF-1(2)VM-
50(125)X/2, IF-1(2)VH-50(125)X/2**

107497, Moscow Chernicinsky pr-d 7/1
Tel.: (495) 775-43-19, 462-44-14
Tel./fax: 462-44-14
E-mail: radial@radial.ru
www.radial.ru

IF-1V-50X/2



IF-1V-125X/2



IF-2V-50X/2



IF-2V-125X/2



Electrical specifications

Model	IF-1VL(VM,VH)-50X/2	IF-2VL(VM,VH)-50X/2	IF-1VL(VM,VH)-125X/2	IF-2VL(VM,VH)-125X/2
Operating frequency band, MHz	VL 140-154 VM 148-163 VH 158-174	VL 140-154 VM 148-163 VH 158-174	VL 140-154 VM 148-163 VH 158-174	VL 140-154 VM 148-163 VH 158-174
Insertion loss not more, dB	0.4	0.8	0.4	0.8
Isolation TX-TX not less, dB	27	55	27	55
Impedance, Ohm	50	50	50	50
VSWR, not more than	1.2	1.2	1.2	1,2
Input power not more than, W	50	50	125	125
Temperature range, °C	from -30 to +50	from -30 to +50	from -30 to +50	from -30 to +50

Mechanical specifications

Model	IF-1VL(VM,VH)-50X/2	IF-2VL(VM,VH)-50X/2	IF-1VL(VM,VH)-125X/2	IF-2VL(VM,VH)-125X/2
Weight, kg	0.48	1.07	1.95	2.35
Connectors	N-female	N-female	N-female	N-female
Length/Width/Depth, mm	125x70x102	150x90x168	480x178x122	480x178x122

Typical isolator characteristics

